



# GDI-7

Description	Specification
<b>Rig Name / Model</b>	GDI-7 / Slingshot type self elevated 1500 HP Drilling rig
<b>Mast Height</b>	154 ft
<b>Hook Load Capacity</b>	1 set 350 Ton elevator links - Size: 2 3/4" x 144" 1 set 250 Ton elevator links - Size: 2 1/4" x 144"
<b>Crown Block</b>	crown-o-matic device
<b>Rig Substructure</b>	29 ft clearance under rotary 33 ft floor height
<b>Set back capacity</b>	550,000 pound setback capacity.
<b>Hook &amp; Block Assembly</b>	SUPERIOR: Model SDS-60-Z-500
<b>Rotary Table</b>	Cameron 37.5" DC Rotary Table, Model L375
<b>Drawworks</b>	Cameron/LEWCO Model LDW750k 750000 lbs, with 12 lines
<b>Top Drive</b>	Canrig 1275AC-681 load rating 750 ton, working pressure 7500
<b>Brakes Mechanism</b>	Air operated caliper Brake model 9L-EC528 + Resistor Brake system
<b>Mud Pump</b>	Weatherford E-1600 5K Type-41 444 @5000PSI , 120RPM & piston size 5,5 inch 1600 HP
<b>Power Package</b>	3XSCR & 3xVFD
<b>Mud System</b>	Shaker, Intermediate, suction 3 tanks x 400 bbl capacity
<b>Shale Shakers</b>	3 x MI-SWACO MD-2 TRIPLE ASSY, 440-480V
<b>Desander</b>	forum pump 2200 rpm , 8 x 6 x 14
<b>Desilter</b>	Ruff model CP864 2200 rpm , 8 x 6 x 14
<b>Degasser</b>	MI Swaco Degasser 1000 GPM
<b>BOP Equipment</b>	NATIONAL OILWELL VARCO

